



P.C.B. LAYOUT(REF)

- NOTES:
1. Rating: 300V 4A
PITCH: 2.50mm
 2. Insulation Withstands Voltage:
AC 1000V/MIN
 3. Insulation Resistance:
500M Ω or more at DC500V
 4. Using Temperature Range:
-40°C~+105°C
 - 5 Suitable Electric Wire: AWG 28~20
 - 6 Undimensioned Tolerances:

—	∩	∇	0.05/10
⊥	∥	≡	0.2/10
DIMENSIONS			0.05/10
TOLERANCES			±0.3



5	END COVER	0119L7XX00	1	PA66	M001
4	LEVER	0119L6XX00	P	POM	W005 W005
3	CLAMP	X000003200	P	STAINLESS STEEL	
2	SOLDER PIN	0119B00300	P	BRASS	TIN PLATED
1	HOUSING	0119N0XX00	P	PA66	M001

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DWG.	DATE	UNITS	MM	SHEET/OF	1/2
CHK.	DATE	SCALE	6:1 (:)		
APP.	DATE				

P	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
U	2.50	5.00	7.50	10.00	12.50	15.00	17.50	20.00	22.50	25.00	27.50	30.00	32.50	35.00	37.50
V	7.20	9.70	12.20	14.70	17.20	19.70	22.20	24.70	27.20	29.70	32.20	34.70	37.20	39.70	42.20
P	17	18	19	20	21	22	23	24							
U	40.00	42.50	45.00	47.50	50.00	52.50	55.00	57.50							
V	44.70	47.20	49.70	52.20	54.70	57.20	59.70	62.20							

Tolerances for PITCH ERROR

REV.	CONTENT	CHK.	DATE
2			



DWG NO. SP-02-WKV250AP
NAME 20.3004M/XX